

# X-403 GT

## CARATTERISTICHE TECNICHE | TECHNICAL CHARACTERISTICS

	VISOR		VISION PROTECTION SYSTEM		VENTILATION SYSTEM		COMFORT PADDING WITH ANTIBACTERIAL TREATMENT		FINISHING																																	
<b>IN THE PRODUCT</b>	SCRATCH RESISTANT TREATMENT ON BOTH SIDES	CONVEX VISOR	ADDITIONAL DARK GREEN VISOR	PINLOCK® WITH ADJUSTABLE PINS	PINLOCK® TYPE	DOUBLE ACTION	QUICK RELEASE SHIELD SYSTEM	VISION PROTECTION SYSTEM WITH SCRATCH RESISTANT AND FOG RESISTANT TREATMENTS ON BOTH SIDES	UV 400 PROTECTION	ADDITIONAL YELLOW VPS	N-COM	HEAD VENTILATION	FRONTAL AIR INTAKE	CHIN GUARD AIR INTAKE	HEAD AIR EXHAUST	SIDE AIR EXHAUST	REAR AIR EXHAUST	BOTTOM TRIM AIR EXHAUST	REMOVABLE CHIN GUARD FILTER	CHIN GUARD	PEAK	PEAK EXTENTION	RETENTION SYSTEM	CAMEL BAG	CARBON FITTING RACING EXPERIENCE COMFORT	UNITHERM® TOURING PERFORMANCE COMFORT	REMOVABLE INTERIOR	STEADYFIT REMOVABLE CHEEK PADS	NERS - NOLAN EMERGENCY RELEASE SYSTEM	EYEWEAR ADAPTIVE	REMOVABLE COMFORT NECK	CHIN STRAP REMOVABLE COMFORT PADDING	WIND PROTECTOR	BREATH DEFLECTOR	VISOR COVERS	CHIN GUARD PLUGS	LUBRI-TRIM KIT	GRAPHICS	WATER BASED PAINT AND TRANSPARENT COATING			
HI-VISIBILITY N-COM	●	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
ELEGANCE N-COM	●	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

N NUOVO SEGMENTO | NEW SEGMENT

△ GRAFICA | GRAPHIC

□ MONOCOLORE CON CALOTTA E MENTONIERA IN COLORE DIFFERENTE | SOLID WITH SHELL AND CHIN GUARD IN DIFFERENT COLOUR

□ FINITURA SPECIALE PER ALCUNI COLORI | SPECIAL FINISHING FOR SOME COLOURS

● MONOCOLORE | SOLID COLOUR

	TAGLIE   SIZES								
TAGLIE DISPONIBILI AVAILABLE SIZES	8	XXS	XS	S	M	L	XL	XXL	XXXL
CALOTTE INTERNE INNER SHELLS (EPS)	6	●	●	●	●	●	●	●	●
CALOTTE ESTERNE OUTER SHELLS (POLYCARBONATE)	3		□		□		□		□
CIRCONFERENZA CIRCUMFERENCE	CM	54	55	56	58	60	62	64	65

## VISIERE DISPONIBILI | AVAILABLE VISORS



METAL BLUE



METAL SILVER



DARK GREEN



SMOKE



CLEAR

COMPATIBILITÀ PRODOTTI N-COM | N-COM COMPATIBILITY

**B90i**  
K SERIES

**BX1**