

X-552

ULTRA CARBON

OMOLOGAZIONE • UN/ECE 22-06

HOMOLOGATION

RETENTION SYSTEM • D-rings

VISIERA • resistente al graffio - ultrawide

VISOR

scratch resistant - ultrawide

• **meccanismo visiera con funzionalita' basculante**

visor mechanism with tilting functionality

• **visierina interna resistente all'appannamento Pinlock®**

Pinlock® fog resistant inner visor

• **schermo parasole VPS (Vision Protection System) regolabile - protezione UV fino a 400nm**

adjustable Vision Protection System (VPS) sunscreen - UV protection up to 400nm

IMBOTTITURA • imbottitura interna di conforto "Carbon Fitting Racing Experience"

INTERNA

con innovativa costruzione a rete

INNER

"Carbon Fitting Racing Experience" inner comfort padding with innovative net construction

PADDING

• **sistema di regolazione della cuffia LPC - Liner Positioning Control**

LPC - Liner Positioning Control

• **NERS - Nolan Emergency Release System**

• **guanciali monoblocco con imbottiture interne sfoderabili**

single-piece cheek pads with removable padding

• **rivestimento stampato dei guanciali interni in polistirolo**

moulded lining for the inner cheek pads in polystyrene

• **EA - Eyewear Adaptive**

• **bandelle sottogola amovibili**

removable chin straps

ALTRE • paravento

CARATTERISTICHE

wind protector

ADDITIONAL

• **deflettore paranaso**

FEATURES

breath deflector

• **guanciali Steadyfit a spessori maggiorati e ridotti (disponibili come ricambio)**

Steadyfit cheek pads with increased and reduced thicknesses (available as spare parts)

n-com

PREDISPOSIZIONE N-COM

SET UP FOR N-COM

• B902 X series

• B602 X series

VISIERE DISPONIBILI

AVAILABLE VISORS

CLEAR

DARK GREEN

METAL BLUE

METAL SILVER

GUANCIALI STEADYFIT

STEADYFIT CHEEK PADS

	RIDOTTO REDUCED	ORIGINALE STANDARD	MAGGIORATO INCREASED
2XS	40 mm	45 mm	-
XS	35 mm	40 mm	45 mm
S	30 mm	35 mm	40 mm
M	25 mm	30 mm	35 mm
L	25 mm	30 mm	35 mm
XL	25 mm	30 mm	35 mm
2XL	20 mm	25 mm	30 mm
3XL	-	20 mm	25 mm